



8600

AudioVideo power supply stabilized with timer cabling Traditional.
 Supply: 230 V a.c., 35 VA.
 Outputs: 16 V a.c., 12 V d.c., 18 V d.c.
 Dimensions: 185x100x77 mm.
 (10,5 DIN modules).

8604

AudioVideo additional power supply, cabling Traditional and Simplified to connect monitors with Image Memory in multi users systems.
 Supply: 230 V a.c., 35 VA,
 Outputs: 18 V d.c., 1 A.
 Dimensions: 185x100x77 mm.
 (10,5 DIN modules).



8843

AudioVideo automatic switch cabling Traditional. For Video systems with 2 main video entrance panels or with 1 main and more stairs video entrance panels.
 Inputs: 18 V d.c.
 Dimensions: 185x100x77 mm.
 (10,5 DIN modules).

ACCESSORIES



2052/E

Audio amplified speaker unit cabling Traditional, with embedded electronic call and call tone feedback.
 Speech volume adjustment.



8050

B/W CCD camera 1/3", lens f.2,0/3,6 mm, 6 IR LEDs for night vision, cabling Traditional, Video outputs signal on coax cable.
 Supply: 18 V d.c.

8050/C

Colour CCD camera 1/4", lens f.3/2,8 mm, cabling Traditional.
 Video outputs signal on coax cable.
 Supply: 18 V d.c.



853

Additional external piezoelectric buzzer.
 Supply: 15 V a.c./d.c.

853/1

External passive call repeater. To connect in systems with electronic call.
 Supply: 15 V a.c./d.c.



859/20

Interface relay with 1 contact 2NO-2NC.
 Supply: 12+24 V a.c./d.c.
 Dimensions: 70x86x71 mm. (3 DIN modules).

859/21

Interface relay with 2 contacts 2NO-2NC + 2NO-2NC.
 Supply: 12+24 V a.c./d.c.
 Dimensions: 70x86x71 mm. (3 DIN modules).



861/4

Active Video distributor 4 outputs cabling Traditional, for video systems with coax cable.
 Amplification: 1 db.
 Supply: 18 V d.c.
 Dimensions: 73x77x26 mm.



SUO/V

Additional buzzer cabling Traditional and Simplified.
 Can be fitted inside the telephone "ELITE".
 Supply: 12/15 V a.c.

SUO/E

Additional tone generator cabling Traditional and for telephone "ELITE PLUS" with more than 3 telephone in parallel.
 Can be fitted inside the telephone "ELITE".